| Camera | | |
|---|--|--|
| Item | Details | |
| Power supply | Using AC adapter: DC 5.2 V Using battery pack: DC 3.6 V | |
| Power con- sumption | 1.8 W (when "LIGHT" is set to "OFF" and "LCD BACKLIGHT" is set to "STANDARD"), Rated Current Consumption: 1.8 A | |
| Dimensions (mm) | 53 x 63 x 110 (2-1/8" x 2-1/2" x 4-3/8") (W x H x D: excluding grip belt) | |
| Mass | Approx. 250 g (0.56 lbs) (camera only), Approx. 280 g (0.62 lbs) (including supplied battery pack) | |
| Operating envi- ronment | Allowable operating temperature: 0°C to 40°C (32°F to 104°F) Allowable storage temperature: -20°C to 50°C (-4°F to 122°F) Allowable operating humidity: 35 % to 80 % | |
| Image pickup device | 1/6" 800.000 pixels | |
| Recording area (Video) | 410.000 pixels (optical zoom) 410.000 to 550.000 pixels (dynamic zoom) | |
| Recording area (Still Image) | 550.000 pixels | |
| Lens | F1.8 to F4.3, f= 2.2 mm to 85.8 mm (35 mm conversion: 41.5 mm to 1,619 mm) | |
| Lowest illumi- nation | 3 lux (Shutter speed: AUTO + AGC) 1 lux (NIGHT EYE mode) | |
| Zoom (during video record- ing) | Optical zoom: Up to 39x Dynamic zoom: Up to 45x Digital zoom: Up to 800x | |
| Zoom (during still image re- cording) | Optical zoom: Up to 39x | |
| LCD monitor | 2.7" wide, 12.3 megapixels, polysilicon color LCD | |
| Recording me- dia | Internal HDD (80 GB), microSD/microSDHC card (commercially available) | |
| Clock battery | Rechargeable battery | |

Video

| Item | Details | |
|------------------------------------|---|--|
| Recording/ Playback for- mat | SD-VIDEO standard, Video: MPEG-2, Audio: Dolby Digital(2ch) | |
| Extension | .MOD | |
| Signal system | NTSC standard | |
| Image quality/ Sound quality | ULTRA FINE : 720 pixels x 480 pixels, 8.5 Mbps VBR (Video), 48 kHz, 384 kbps (Audio) FINE : 720 pixels x 480 pixels, 5.5 Mbps VBR (Video), 48 kHz, 384 kbps (Audio) NORMAL : 720 pixels x 480 pixels, 4.2 Mbps VBR (Video), 48 kHz, 256 kbps (Audio) ECONOMY : 352 pixels x 240 pixels, 1.5 Mbps VBR (Video), 48 kHz, 128 kbps (Audio) | |

Still Image

| 5 | |
|------------|-----------------------|
| Item | Details |
| Format | JPEG standard |
| Extension | JPG |
| Image size | 832 × 624 / 640 × 480 |
| Quality | FINE / STANDARD |

AC Adapter (AP-V30U)

| | - |
|---|--|
| Item | Details |
| Power supply | AC 110 V to 240 V, 50 Hz/60 Hz |
| OUTPUT | DC 5.2 V, 1.8 A |
| Allowable oper- ating tempera- ture | 0°C to 40°C (32°F to 104°F) (10°C to 35°C (50°F to 95°F) during charging) |
| Dimensions (mm) | 78 x 34 x 46 (3-1/8" x 1-3/8" x 1-13/16") (W x H x D: excluding cord and AC plug) |
| Mass | Approx. 107 g (0.24 lbs) |

Battery Pack (BN-VG107U)

| Item | Details |
|--------------------|---|
| Power voltage | 3.6 V |
| Capacity | 700 mAh |
| Dimensions (mm) | 31 x 21.5 x 43 (1-1/4" x 7/8" x 1-3/4") (W x H x D) |
| Mass | Approx. 26 g (0.06 lbs) |